

Internet Software Technologies

HTML

IMCNE

A.A. 2008/09

Gabriele Cecchetti

The Web

- WWW: network of information systems.
- Information unit: documents or pages.
- Web pages can link other documents containing related information:
 - hypertext,
 - hypermedia
- Client-server architecture: web servers -browser
- Main protocol used: **http**
- Client applications to access web pages: **browser**
- Web sites hosts server programs called **http server**.

Web foundation

1. *Naming scheme based on URLs*
 2. *Network protocol: HTTP*
 3. Languages to describe information content: **HTML**
-

3

URL

- Composed by:
 1. protocol followed by “://”,
 2. address of web-site,
 3. resource path.
- Example:
 - <http://retis.sssup.it/~gabriele/Teaching/IST>
(where you will find course material)

4

HTTP - HyperText Transfer Protocol

- HTTP defines a Request-response chat, composed by:
 - 1) Client establish a connection with the server and ask for a document;
 - 2) Server answer using the same connection.
- The protocol is *stateless*

5

HTML - Hyper Text Markup Language

- It's a Markup Language, used to describe the contents of a document.
- By using HTML you may publish document with:
 - Headings, Paragraphs, Lists,
 - Tables,
 - Images,
 - Hypertext
 - Forms for search and transactions
 - Hypermedia

6

HTML standard

- Defined by W3 consortium: <http://www.w3.org/>
- HTML is only for contents.
- Use CSS to better format your documents.

7

First HTML document: Hello world!

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN"  
"http://www.w3.org/TR/html4/strict.dtd">  
<HTML>  
  <HEAD>  
    <TITLE> My first HTML page </TITLE>  
  </HEAD>  
  <BODY>  
    <P> Hello world! </P>  
  </BODY>  
</HTML>
```

8

HTML Elements

Start Tag *<element-name>*

Content

Final Tag *</element-name >*

- Some elements may be used
 - without final (P, LI),
 - other may be used without start tag (HEAD, BODY),
 - others do not have content (BR)

9

HTML attributes

- Example

```
<A HREF="file.html">A file </A>
```

- HREF is an attribute of A Element
- file.html is the value of HREF attribute
- An Element may have several attributes

10

Comments

```
<!-- one line comment -->  
<!-- multiple line  
comment -->
```

11

HTML document: global structure

- 3 parts:
 - Version Line
 - Head section
 - Body section

12

HTML Version

- **Version line** specifies the *Document Type Definition* (DTD) used for the document.

- Example:

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01  
Frameset//">
```

- Sometimes affect the presentation of the page

13

<HEAD>

- HEAD element hold information about the current document:
 - Title
 - Keywords
 - Meta information

14

<TITLE>

- TITLE belong to HEAD section
- TITLE should be used to give a title to a document

15

<META>

(1/2)

- META belongs to HEAD section
- It gives information about the document

```
<META name="Author" content="Dave Raggett">
<META name="keywords" lang="en"
      content="holiday, Greece, sunshine">
<META name="description" content="some
      description">
<META http-equiv="Content-Type"
      content="text/html; charset=ISO-8859-15">
```

16

- Meta information is used to add HTTP protocol headers

```
<META http-equiv="Expires" content="Thu, 01  
Jan 2004 14:25:27 GMT">  
<META http-equiv="Refresh" content="10">  
<META http-equiv="Refresh"  
content="10;URL=http://localhost/pag2.html">
```

- Attributes (deprecated)
 - **background** = *uri*
 - **bgcolor** = *color*
 - **text** = *color*
 - **link** = *color*
 - **vlink** = *color*
 - **alink** = *color*
- Every element and attribute which affects the page rendering is deprecated; you should use the CSS!

Headings

- **H1, H2, H3, H4, H5, H6**

- Example:

```
<h1> Chapter 1 </h1>
```

```
<h2> Section 1 </h2>
```

```
<p> This is the first paragraph </p>
```

```
...
```

19

Structured Text

- **EM, STRONG, DFN, CODE, SAMP, KBD, VAR, CITE, ABBR e ACRONYM**
- **BLOCKQUOTE e Q**
- **SUB e SUP**
- **Typographical Elements (*deprecated*)**
 - **B, I, TT, U**

20

Paragraphs

- **<P>**
 - To break a line:

 - To avoid braking a line:
- Preformatted text: <PRE>

21

Lists

- ** Unordered List**, list items defined by
 - Attributes (*deprecated*):
type= disc | square | circle
- ** Orderd List**, list items defined by
 - Attributes (*deprecated*):
type= 1 | i | I | A | a
start=[1..]
- **<DL> Definition List**
 - <DT> Definition Term </DT>
 - <DD> Definition Data </DD>

22

Tables: an example

```
<TABLE border="1">  
<CAPTION><EM>Table example</EM></CAPTION>  
<TR><TH rowspan="2"><TH colspan="2">Media  
<TH rowspan="2">Eyes<BR>red  
<TR><TH>Height<TH>Weight  
<TR><TH>Males<TD>1.9<TD>0.003<TD>40%  
<TR><TH>Females<TD>1.7<TD>0.002<TD>43%  
</TABLE>
```

23

<TABLE>

- <TABLE>
 - **align = left | center | right**
 - **width = *length***
- <CAPTION>
 - **align = left | center | right**

24

TR, TH, TD

- TR attributes:
 - **width** = *length*
 - **height** = *length*
 - **align**, **valign**
- TH, TD attributes:
 - **rowspan** = *number*
 - **colspan** = *number*
 - **nowrap**
 - **width** = *length*
 - **height** = *length*
 - **align**, **valign**

25

ROWSPAN e COLSPAN

- Examples

26

Other tables attributes

- **frame** = void | above | below | hsides | lhs | rhs | vsides | box | border
- **rules** = none | groups | rows | cols | all
- **border** = *pixels*
- **align** = left | center | right | justify
- **valign** = top | middle | bottom | baseline
- **cellspacing** = *length*
- **cellpadding** = *length*

27

Hyperlinks

```
<BODY>
<P> Look at
<A href="http://www.sssup.it/"> SSSUP
    </A> site, and then this
<A href="..../immages/pisa.gif"> city
    map</A>.
</BODY>
```

28

Anchor

- It may be the starting point of an hyperlink (when has **href** attribute) and/or the destination point of an hyperlink (when has the name attribute)
- The destination point of an hyperlink may be described by:
 - ;
 - **id** attribute: <H1 id="nomeancora">

29

Anchor inside a page

```
<H1> Summary</H1>
<P>
<A href="#section1">Introduction</A><BR>
<A href="#section2">Basic concepts</A><BR>
<A href="#section2.1">First concept</A><BR>
...
<H2><A name="section1">Introduction</A></H2>
... section 1 ...
<H2><A name="section2">Basic concepts</A></H2>
... section 2 ...
<H3 id="sezione2.1">First concept</A></H3>
... section 2.1 ...
...
```

30

- To put images on web page use IMG element
- src attribute specifies the URL containing the image.

- Example:

```
<IMG name="my_cats" src="/images/mycats.gif"  
     alt="A photo of my cats">
```

31

Image Maps

- Image maps let to specify image regions assigning an action for every region specified.
 - Client-side Image Maps
 - Server-side Image Maps (usually not adopted)

32

Client-side Image map

```
<P>To visit this site:  
<IMG SRC="navbar1.gif" usemap="#map1">  
<MAP name="map1">  
<AREA href="home.html" alt="Homepage"  
      shape="rect" coords="0,0,118,28">  
<AREA href="whoami.html" alt="Who am I ?"  
      shape="rect" coords="118,0,184,28">  
<AREA href="search.html" alt="Search"  
      shape="circle" coords="184,200,60">  
<AREA href="help.html" alt="Help" shape="poly"  
coords="276,0,276,28,100,200,276,0">  
</MAP></P>
```

33

Images border (deprecated)

```
<IMG src="cat.gif" border=1>
```

34

Image Align (deprecated)

```
<IMG src="cat.gif" align="middle">
```

- **Align** may have the following values:
 - **bottom**: image bottom is vertical aligned with current base line (default)
 - **middle**: image middle is vertical aligned with current base line
 - **top**: image top is vertical aligned with current base line
 - **left | right**: image is align to left or right margin of the page

35

Text align (deprecated)

```
<P align=center>centered paragraph</P>
```

- Where:
align = left | center | right | justify

36

Font (*deprecated*)

```
<FONT SIZE=1>something</FONT>
<FONT SIZE=+1>something</FONT>
<FONT FACE="Times">something</FONT>
<FONT COLOR="red">something</FONT>
```

37

FRAMES – An Example (1/2)

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Frameset//EN"
"http://www.w3.org/TR/html4/frameset.dtd">
<HTML>
<HEAD>
<TITLE> FRAMES – An Example </TITLE>
</HEAD>
<FRAMESET cols="20%, 80%">
<FRAME name="index" src="frame_index.html">
<FRAMESET rows="100, 200">
<FRAME name="top" src="logo.html">
<FRAME name="main" src="content.html">
</FRAMESET>
</FRAMESET>
```

38

FRAMES – An Example (2/2)

```
<NOFRAMES>
<!-- Content for not-supporting FRAMES browser --&gt;
...
&lt;/NOFRAMES&gt;
&lt;/FRAMESET&gt;
&lt;/HTML&gt;</pre>
```

39

FRAME: attributes

- **name** = *frame_name*
- **longdesc** = *url*
- **src** = *url*
- **noresize**
- **scrolling** = *auto|yes|no*
- **frameborder** = *1|0*
- **marginwidth** = *pixels*
- **marginheight** = *pixels*

40

HyperLinks' Target of a frame

```
<A href="slide3.html" target="main">  
slide 3 </A>
```

- Special target
 - target="_parent"
 - target="_top"